

# TECHNICAL DATA SHEET

## ACF line

The ACF – Series are small ozone generators with various ozone outputs. The ozone flows in a PTFE tube, and thus allowing easy transport to the point of use. Possible to control (optional) ozone concentration by: Sensor (automatic) or regulator (manual).

	ACF-1000	ACF-2000	ACF-3000	ACF-4000
Ozone concentration output*	1,0 g/h	2,0 g/h	3,0 g/h	4,0 g/h
Energy consumption	75 W	100 W	130 W	160 W
Dimensions (HxWxD)	290 x 170 x 130mm	350 x 280 x 140mm	350 x 280 x 140mm	350 x 280 x 140mm
Weight	3,2 kg	5,0 kg	6,0 kg	7,0 kg
Ozone production technique	Quartz-tube			
Supply Voltage	230 V / 50 Hz			
Mounting	Wall mounted or free standing			
External connections	Standard: On/off Optional: Safety sensor, regulator or 0-100%			
Ozone output	PTFE tube connector Ø 6 mm			
Operation condition	-10° to + 35 ° C (optim. 15° C) - <50% rH			
Cover	Stainless steel			
Warranty**	1 year limited warranty			

\*Relative to ambient conditions. All technical changes and upgrades are reserved INFUSER

\*\*See warranty conditions

